

e-STUDIO™ 232/282



Value. Versatility. Functionality.

The perfect match for any document workflow.



TOSHIBA
Don't copy. Lead.

SPECIFICATIONS	
Copying Process	Indirect Electrostatic Photographic Method (Dry Process)
Copying Type	Laser Electronic
Original Reading Method	CCD Line Sensor
Copy/Print Resolution	2400 x 600 dpi (with smoothing)
Copy/Print Speed	e-STUDIO232 – 23 PPM (Letter) e-STUDIO282 – 28 PPM (Letter)
Warm-Up Time	Approx. 25 Seconds
First Copy Out Time	Less Than 5.4 Seconds (Letter)
Duty Cycle	e-STUDIO232 – 74,000 Copies e-STUDIO282 – 90,000 Copies
Multiple Copying	Up to 999 Copies
Acceptable Paper Size	Cassette: Statement-R to Ledger (17-28 lbs.) Bypass: Statement-R to 12" x 18" (17-110 lbs.) LCF: Letter (17-28 lbs.)
Acceptable Paper Type	Standard Bond, Overhead Transparencies, Gummed Labels
Processor	Power PC 750 CXr/333 MHz Shared
Memory	Main Memory: 256 MB / Page Memory: 32MB/40GB+ (HDD)
Reduction/Enlargement	25% to 400%
Bypass	Stack Feed "Smart" Bypass (100-Sheet)
Control Panel	Half VGA Tilttable LCD Touch Panel, Key Top
Paper Supply	Up to 3,700-Sheet Input Capacity Standard: 2 x 550-Sheet Cassettes (17-28 lbs.) Optional: 1 x 550-Sheet PFP, 1 x 550 Sheet Cassette, 1 x 2,500-Sheet LCF
Toner Control Method	Automatic Toner Density Monitoring
Dimensions	Approx. 26" x 28" x 29"
Weight	Approx. 165 lbs.
Minimum Footprint Requirement	39.53" x 28.31" (W x D)
PM Cycle	74,000/90,000
Drum Type/Yield	Organic Photoconductor/74,000/90,000
Black Toner Yield	23,000
Black Developer Yield	74,000/90,000
Power Supply	115 V, 15 Amps
Power Consumption	Maximum 1.5 kW

PRINT	
PDL Support	PCL6 & PostScript 3
Operating Systems	Netware 4.x, 5.x, 6.x, Windows Me/2000/XP, Windows NT 4.0, Windows Server 2003, Citrix MetaFrame, Macintosh, Linux, UNIX
Protocol Support	IPX/SPX, TCP/IP, EtherTalk, AppleTalk, NetBIOS Over TCP/IP, LPR/LPD, IPP, SMB, SNMP, Netware, Port 9100, Bluetooth (HCRP)
Drivers	Windows Me, 2000, Server 2003, XP, NT 4.0, Macintosh OS 8.6, 9.x, 10.1/10.2/10.3 (with PPD), UNIX, AS400 via iData & Port 9100, SAP R/3
Connectivity	10BaseT/100BaseTX Ethernet, 802.11b/g Wireless LAN, USB 2.0, Bluetooth (HCRP)
Device Management	TopAccess
Certification	WHQL, Novell



SCAN	
Scan Resolution	150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan Speed	50 OPM (Letter)
File Format	TIFF-MMR, TIFF-S, PDF, JPEG
Authentication	LDAP, SMTP

FACSIMILE	
Compatibility	Super G3, G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	33.6 Kbps
Fax Memory	Transmission 500 MB (HDD), Reception 120 MB (HDD) 40GB+ (HDD) Back-Up
Memory Transmission	100 Jobs, 1,000 Destinations Max., 400 Destinations/Job
Scan Speed	.7 Seconds Per Page, 50 Scans Per Minute

e-FILING	
Operation Method	Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder, 200 Pages Per Document
File Format	TIFF-MMR, PDF, TAC

OPTIONS	
MR3020 Reversing Auto Document Feeder (RADF)	Simplex Originals (9.3-41.8 lbs.) Duplex Originals (13.3-41.8 lbs.)
KD1011 Paper Feed Pedestal	550-Sheet Pedestal, Statement-R to Ledger (17-28 lbs.)
MY1021 Cassette Module	550-Sheet Drawer, Statement-R to Ledger (17-28 lbs.)
KD1012 Large Capacity Feeder (LCF)	2,500-Sheet Drawer, Letter (17-28 lbs.) Stacks Side-By-Side (2 x 1,250)
MJ5004 Job Separator	Attaches to Inner Exit Compartment Upper Tray: 150-Sheet Capacity Lower Tray: 250-Sheet Capacity
MJ5005 Offset Catch Tray	Attaches to Inner Exit Compartment 250-Sheet Paper Capacity
MJ1022 Single-Position Stapling Finisher	2 Tray, Hanging Design Tray 1 Stack Capacity: 200 Sheets (Lt) Tray 2 Stack Capacity: 700 Sheets (Lt) Staple Capacity: 30 Sheets (Lt/Lt-R, 20 lbs.)
MJ1025 Multi-Position Stapling Finisher With Saddle-Stitch	2 Tray + Saddle-Stitch Tray, Console Design Tray 1 Stack Capacity: 1,000 Sheets (Lt) Tray 2 Stack Capacity: 1,000 Sheets (Lt) Staple Capacity: 50 Sheets (Lt/Lt-R, 20 lbs.)
MJ6005 Hole Punch Unit	(for MJ1025) 2- or 3-Hole Punch Capability
KN3520 Bridge Kit	Required with MJ1022, MJ1023, MJ1025
KA3511 Platen Cover	
KK3511 Work Tray	
GM1070 Print Enabler	
GM2070 Print & Scan Enabler	
GM4070 Scan Upgrade Enabler	
GD1150 Fax Board	
GD1160 2nd PSTN Line	
GN1041 Wireless LAN Adapter	
GN2010 Bluetooth Module	
GN3010 Antenna	
GP1040 Scrambler Board	
G01060 PCI Slot for Scrambler Board	
GP1060 Data Overwrite Kit	
GQ1020 Coin Controller Wiring Harness	

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates, based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

AUTHORIZED TOSHIBA DEALER

Corporate Office: 2 Musick, Irvine, CA 92618-1631

East Coast: 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973/316-2700 Fax: 973/263-2393

Midwest: 8770 W. Bryn Mawr Ave., Suite 700, Chicago IL 60631

Tel: 773/380-6000 Fax: 773/380-8077

South: 4855 Peachtree Industrial Blvd., Suite 210, Norcross, GA 30092-3024

Tel: 770/209-8540 Fax: 770/209-8556

West Coast: 142 Technology, Suite 150, Irvine, CA 92618

Tel: 949/462-6262 Fax: 949/462-2700

Web Site: www.copiers.toshiba.com or www.fax.toshiba.com.

© 2006 Toshiba America Business Solutions, Inc., Electronic Imaging Division

e-STUDIO232/282 Spec Sheet/Inv. Code ES2322822

TOSHIBA
COPY • FAX • PRINT